

ODR 500 Diamond Drill Rig

TECHNICAL SPECIFICATIONS

Features:

- · Powerful and practical design for high production and low operational costs
- Operator Friendly controls designed and built with the driller in mind
- Guarding exceeds industry standards
- Modular build for ease of helicopter mobilization and difficult to access projects
- Fits into 20ft shipping container no disassembly required
- Proven and tested for reliability in extreme environments and difficult drilling conditions



Specifications

Depth Rating	BO	1100 m (3600 ft)
	NO	800 m (2600 ft)
	HO	500 m (1600 ft)
	PO	350 m (1150 ft)
Rotation Unit Options	Hollow Spindle 'P' or 'H' 2 speedVariable hydraulic motor	
Mast	 Folding design 6m (20ft) Pull Mast dump feature for safe and efficient setup with 1.5m (60" travel) Hydraulic rod centralizer integrated in mast assembly Hydraulic hose track system for safe and protected operation 	
Foot Clamp	 Reliable and practical - 2 jaw design Hydraulic syncronized with chuck function PW/PWT Capacity 	
Wireline Hoist	• Level-wind 1500m (4900 ft) - 3/16" cable capacity	
Hydraulic System	 High quality pressure compensated hydraulic system with industry leading filtration Hydraulic mud mixer Hydraulic power 435 flush pump 	
Mainline Hoist	 Pullmaster (Made in Canada) 12000 lb single line pull 	





